

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL PUBLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : C09K 5/04	A1	(11) International Publication Number: WO 93/15163 (43) International Publication Date: 5 August 1993 (05.08.93)
(21) International Application Number: PCT/US93/00862 (22) International Filing Date: 2 February 1993 (02.02.93) (30) Priority data: 829,848 3 February 1992 (03.02.92) US (71) Applicant: ALLIED-SIGNAL INC. [US/US]; 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US). (72) Inventors: HARNISH, Daniel, Franklin ; 77 Middlebury Road, Orchard Park, NY 14127 (US). LUND, Earl, August, Eugene ; 404 Reserve Road, West Seneca, NY 14224 (US). SHANKLAND, Ian, Robert ; 200 Forest Hill Drive, Williamsville, NY 14220 (US). SINGH, Rajiv, Ratna ; 147 Palmdale Drive, Williamsville, NY 14221 (US). WILSON, David, Paul ; 118 Waxwing Court, East Amherst, NY 14051 (US).		(74) Agent: FUCHS, Gerhard, H.; Allied-Signal Inc., Law Department (C.A. McNally), 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US). (81) Designated States: AU, BR, CA, JP, KR, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: NOVEL REFRIGERANT COMPOSITIONS (57) Abstract Compositions comprising 1,1,1,2-tetrafluoroethane, pentafluoroethane and a member selected from the group consisting of 1,1-difluoroethane, propane and trifluoromethane, having a vapor pressure from about 12.2 psia to about 18.4 psia at -40 °F.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

NOVEL REFRIGERANT COMPOSITIONS

5

BACKGROUND OF THE INVENTION

Fluorocarbon based fluids have found widespread use in industry for refrigeration, air conditioning and heat pump applications.

10

Vapor compression cycles are one common form of refrigeration. In its simplest form, the vapor compression cycle involves changing the refrigerant from the liquid to the vapor phase through heat
15 absorption at a low pressure, and then from the vapor to the liquid phase through heat removal at an elevated pressure.

20

While the primary purpose of refrigeration is to remove energy at low temperature, the primary purpose of a heat pump is to add energy at higher temperature. Heat pumps are considered reverse cycle systems because for heating, the operation of the condenser is inter-
changed with that of the refrigeration evaporator.

25

The art is continually seeking new fluorocarbon based fluids which offer alternatives for refrigeration and heat pump applications. Currently, of particular interest, are fluorocarbon based mixtures which are
30 considered to be environmentally acceptable substitutes for the presently used chlorofluorocarbons. The latter, such as monochlorodifluoromethane (HCFC-22) are suspected of causing environmental problems in connection with the earth's protective ozone layer.

35

-2-

The substitute materials must also possess those properties unique to the chlorofluorocarbons including similar refrigeration characteristics, chemical stability, low toxicity, non-flammability, efficiency
5 in-use and low temperature glides.

By "similar refrigeration characteristics" is meant a vapor pressure which is plus or minus 20 percent of the reference refrigerant at the same
10 temperature.

The characteristic of efficiency in-use is important, for example, in air conditioning and refrigeration where a loss in refrigerant thermodynamic
15 performance or energy efficiency may have secondary environmental impacts through increased fossil fuel usage arising from an increased demand for electrical energy.

20 Low temperature glides have the following described significance. The condensation and evaporation temperatures of single component refrigerant fluids are defined clearly. If the small pressure drops in the refrigerant lines are ignored,
25 the condensation or evaporation occurs at a single temperature corresponding to the condenser or evaporation pressure. For mixtures employed as refrigerants, there is no single phase change temperature but a range of temperatures. This range is
30 governed by the vapor-liquid equilibrium behavior of the mixture. This property of mixtures is responsible for the fact that when non-azeotropic mixtures are used in the refrigeration cycle, the temperature in the condenser or the evaporator has no longer a single
35 uniform value, even if the pressure drop effect is

-3-

ignored. Instead, the temperature varies across the equipment, regardless of the pressure drop. In the art this variation in the temperature across an equipment is known as temperature glide.

5

For non-isothermal heat sources and heat sinks, this temperature glide in mixtures can be utilized to provide better efficiencies. However in order to benefit from this effect, the conventional
10 refrigeration cycle has to be redesigned, see for example T. Atwood "NARBS - The Promise and the Problem", paper 86-WA/Ht-61 American Society of Mechanical Engineers. In most existing designs of refrigeration equipment, a temperature glide is a cause
15 of concern. Therefore non-azeotropic refrigerant mixtures have not found wide use. An environmentally acceptable non-azeotropic mixture with a small temperature glide and with a similar refrigeration capacity to other known pure fluids, such as HCFC-22
20 would advance the art.

1,1,1,2-Tetrafluoroethane (HFC-134a) is considered to be an environmentally acceptable refrigerant but it is much less volatile than HCFC-22 and consequently
25 offers a much lower refrigeration capacity than HCFC-22. Use of HFC-134a as an alternative for HCFC-22 would require significant and costly equipment redesign. Moreover, at lower evaporating temperatures, HFC-134a exhibits a subatmospheric vapor pressure.
30 System leaks would result in an influx of air causing performance and reliability deterioration.

Pentafluoroethane (HFC-125) is also considered to be an environmentally acceptable refrigerant. However,
35 its critical temperature is very low, about 54°F lower

-4-

than that of HCFC-22. Because of this low critical temperature, the refrigeration capacity of HFC-125 drops at high condensing temperatures and a system using HFC-125 becomes very inefficient.

5

1,1-Difluoroethane (HFC-152a) and propane are environmentally acceptable fluid but are very flammable.

10

Trifluoromethane (HFC-23) is also environmentally acceptable but has a room temperature critical point making it impractical in any HCFC-22 application.

DESCRIPTION OF THE INVENTION

15

In accordance with the invention, novel non-azeotropic compositions have been discovered comprising HFC-134a, HFC-125 and a member selected from the group consisting of HFC-152a, propane and HFC-23, having a vapor pressure of about 12.2 psia to about 18.4 psia at -40°F.

20

When the selected member is HFC-152a, the compositions comprise from about 15 to about 70 mole percent HFC-134a, from about 30 to about 85 mole percent HFC-125 and from about 1 to about 35 mole percent HFC-152a. The preferred compositions are from about 20 to about 45 mole percent HFC-134a, from about 40 to about 70 mole percent HFC-125 and from about 2 to about 25 mole percent HFC-152a.

30

When the selected member is propane, the compositions comprise from about 15 to about 70 mole percent HFC-134a, from about 30 to about 85 mole percent HFC-125 and from about 1 to about 12 mole

35

-5-

percent propane. The preferred compositions are from about 20 to about 45 mole percent HFC-134a, from about 40 to about 70 mole percent HFC-125 and from about 2 to about 10 mole percent propane.

5

When the selected member is HFC-23, the compositions comprise from about 30 to about 95 mole percent HFC-134a, from about 1 to about 75 mole percent HFC-125 and from about 1 to about 10 mole percent HFC-
10 23. The preferred compositions are from about 40 to about 80 mole percent HFC-134a, from about 40 to about 60 mole percent HFC-125 and from about 2 to about 5 mole percent HFC-23.

15 The HFC-134a, HFC-125, HFC-152a, propane and HFC-23 components of the novel compositions of the invention are all known materials and are either commercially available or may be prepared by known methods. Preferably they should be used in
20 sufficiently high purity so as to avoid the introduction of adverse influences upon the properties of the system.

Additional components may be added to the
25 compositions to tailor the properties according to the need, for example, additional refrigeration components, hydrocarbons to aid oil solubility if not already present and additives, such as lubricants.

30

The novel compositions of the invention satisfy the above-identified objectives for being a replacement for HCFC-22. The compositions are generally non-flammable; however, certain compositions within the
35 broad scope of the invention may be flammable and may

-6-

be avoided if desired. Flammability may readily be measured by an ASTM E-681 apparatus. Calculation of the thermodynamic properties of these compositions show that the refrigeration performance is substantially the same as that of HCFC-22.

In addition to having zero ozone depletion potential and providing a good match for the capacity of HCFC-22, the novel compositions of the invention provide the additional advantages of having a higher critical temperature than that of HFC-125. The higher critical temperature translates to improved energy efficiency in a refrigeration or air conditioning cycle, especially at high condensing temperatures. The temperature glide that occurs on evaporation and condensation with non-azeotropic refrigerants is smaller for the compositions containing propane than for the binary combination of HFC-134a and HFC-125 disclosed in the prior art.

20

In one process embodiment of the invention, the compositions of the invention may be used in a method for producing refrigeration which involves condensing a refrigerant comprising the compositions and thereafter evaporating the refrigerant in the vicinity of the body to be cooled.

In another process embodiment of the invention, the compositions of the invention may be used in a method for producing heating which involves condensing a refrigerant comprising the compositions in the vicinity of the body to be heated and thereafter evaporating the refrigerant.

-7-

Example 1

The theoretical performance of a refrigerant at specific operating conditions can be estimated from the thermodynamic properties of the refrigerant using standard refrigeration cycle analysis techniques, see for example, "Fluorocarbons Refrigerants Handbook", Ch. 3, Prentice-Hall (1988), by R.C. Downing. The coefficient of performance, COP, is a universally accepted measure, especially useful in representing the relative thermodynamic efficiency of a refrigerant in a specific heating or cooling cycle involving evaporation or condensation of the refrigerant. In refrigeration engineering this term expresses the ratio of useful refrigeration to the energy applied by the compressor in compressing the vapor. The capacity of a refrigerant represents the volumetric efficiency of the refrigerant. To a compressor engineer this value expresses the capability of a compressor to pump quantities of heat for a given volumetric flow rate of refrigerant. In other words, given a specific compressor, a refrigerant with a higher capacity will deliver more cooling or heating power. A similar calculation can also be performed for non-azeotropic refrigerant blends.

Theoretical performance calculations for an air conditioning refrigeration cycle where the average temperature is typically 115°F and where the average evaporator temperature is typically 40°F are performed using these standard techniques. Isentropic compression and a compressor inlet temperature of 60°F are assumed. Calculations show that blends of the current invention match the capacity of HCFC-22, offer very similar COPs (Coefficient of Performance) and

-8-

exhibit discharge temperatures significantly lower than HCFC-22. The temperature glide is determined not to exceed 11°F which is minor. According to the known art (D.A. Didion and D.B. Bivens "The role of Refrigerant Mixtures as Alternatives" in CFC's: Today's Options...Tomorrow's Solutions, NIST, 1990) temperature glides of the order of 6 to 7°F are minor. The temperature glide here is 9 to 11°F. Therefore the temperature glide of the compositions claimed herein is considered small in this art and need not pose a problem for conventional refrigeration units.

-9-

We claim:

1. Compositions comprising 1,1,1,2-tetrafluoroethane, pentafluoroethane and a member selected from the group consisting of 1,1-difluoroethane, propane and trifluoromethane, having a vapor pressure from about 12.2 psia to about 18.4 psia at -40°F.
2. Compositions according to claim 1 consisting essentially of the components recited.
3. Compositions according to claim 1 comprising from about 15 to about 70 mole percent 1,1,1,2-tetrafluoroethane, from about 30 to about 85 mole percent pentafluoroethane and from about 1 to about 35 mole percent 1,1-difluoroethane.
4. Compositions according to claim 3 comprising from about 20 to about 45 mole percent 1,1,1,2-tetrafluoroethane, from about 40 to about 70 mole percent pentafluoroethane and from about 2 to about 25 mole percent 1,1-difluoroethane.
5. Compositions according to claim 1 comprising from about 15 to about 70 mole percent 1,1,1,2-tetrafluoroethane, from about 30 to about 85 mole percent pentafluoroethane and from about 1 to about 12 mole percent propane.
6. Compositions according to claim 5 comprising from about 20 to about 45 mole percent 1,1,1,2-tetrafluoroethane, from about 40 to about 70 mole percent pentafluoroethane and from about 2 to about 10 mole percent propane.

-10-

7. Compositions according to claim 1 comprising from
about 30 to about 95 mole percent 1,1,1,2-tetra-
fluoroethane, from about 1 to about 75 mole
percent pentafluoroethane and from about 1 to
5 about 10 mole percent trifluoromethane.
8. Compositions according to claim 7 comprising from
about 40 to about 80 mole percent 1,1,1,2-tetra-
fluoroethane, from about 40 to about 60 mole
10 percent pentafluoroethane and from about 2 to
about 5 mole percent trifluoromethane.
9. The method for producing refrigeration which
comprising condensing a composition of claim 1 and
15 thereafter evaporating the composition in the
vicinity of a body to be cooled.
10. The method for producing heating which comprises
condensing a composition of claim 1 in the
20 vicinity of a body to be heated and thereafter
evaporating said composition.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 93/00862

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate)

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 C09K5/04

II. FIELDS SEARCHEDMinimum Documentation Searched⁷

Classification System

Classification Symbols

Int.Cl. 5

C09K

Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched⁸**III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹**

Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X	EP,A,0 430 170 (MATSUSHITA ELECTRIC) 5 June 1991 see page 3, line 5 - line 6 see page 3, line 28 - line 34 see figure 5; example 5 ---	1-4, 9, 10
X	EP,A,0 430 169 (MATSUSHITA ELECTRIC) 5 June 1991 see page 2, line 5 - line 6 see page 2, line 28 - line 34 see figure 3; example 3 ---	1, 2, 7, 9, 10
X	PATENT ABSTRACTS OF JAPAN vol. 15, no. 413 22 October 1991 & JP,A,31 70 590 (MATSUSHITA ELECTRIC) see abstract --- -/-	1-3

¹⁰ Special categories of cited documents : ¹⁰

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

13 MAY 1993

Date of Mailing of this International Search Report

28. 05. 93

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

PUETZ C.

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
X	DATABASE WPIL Week 9136, Derwent Publications Ltd., London, GB; AN 91-262364 & JP,A,3 170 594 (MATSUSHITA) 24 July 1991 see abstract	1,2
A	---	7
X	EP,A,0 451 692 (DAIKIN INDUSTRIES) 16 October 1991	1,2
A	see page 2, line 3 - line 32; figure 2; example 2 -----	3,4

ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

US 9300862
SA 70073

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13/05/93

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0430170	05-06-91	JP-A- 3170584	24-07-91
		JP-A- 3170587	24-07-91
EP-A-0430169	05-06-91	JP-A- 3170585	24-07-91
		JP-A- 3172385	25-07-91
EP-A-0451692	16-10-91	JP-A- 3287688	18-12-91
		AU-A- 7407691	10-10-91